

AQUASEAL

RESILIENT FLOOR SEALER

TDSE19-1-1100

PRODUCT INFORMATION DATA

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

DESCRIPTION: -

AQUASEAL is an all resin, emulsified water based, polyacrylic sealer. It is the recommended sealer undercoat for use on vinyl, linoleum, and rubber and is suitable for terrazzo as a prerequisite for a good floor treatment schedule.

AQUASEAL offers good filling properties to porous floors and provides an even surface to which polishes and finishes can be applied to Linoleum, vinyl and rubber should be treated with AQUASEAL as a seal coat prior to polishing with Duraglo Wax Polish or metallised acrylic polishes such as Sintilate, Gemini, Supreme, Challenge and Metallised Duraglo.

PHYSICAL PROPERTIES

Appearance	Opaque white liquid
Odour	Acrylic polymer
pH	8.0 – 9.0
Specific Gravity	1.035 ± 0.005
Percentage Volatiles	81 – 83%
Solubility in Water	40 – 50 m ² /litre (typical)

DIRECTIONS FOR USE: -

Thoroughly clean the floor surface and remove all traces of dirt, wax and polish accumulation. The use of a Peerless Stripping Emulsion to thoroughly clean the floor is recommended. Pick up all slurry and thoroughly rinse the floor to ensure a clean surface and allow to dry.

Apply AQUASEAL in a thin even coat with a clean cotton mop or lambswool applicator; avoid leaving pools. Under normal conditions, one coat is sufficient to adequately seal the surface. On old or very porous floors a second application may be desirable. On drying apply 2 coats of an approved Peerless wax or sealer finish. Do not allow traffic on the floor until the job is complete and the final coat is completely dry.

REMOVABILITY: -

When it is considered necessary, the complete film can be removed with Peerless Floor Stripping Emulsion ST 9, or Peerless Lazer Super ST 26.

TDGLA 001

PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.

N.S.W. (02) 9674 3000 QLD. (07) 3260 1377 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219

Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421