

ELEGANCE

ULTRA HIGH SPEED FLOOR SEALER FINISH

TDWE64-1-1100

PRODUCT INFORMATION DATA

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

DESCRIPTION: -

ELEGANCE Floor Sealer Finish utilizes the advances in acrylic coating technology to produce a floor finish that provides exceptional wear resistance with a pleasing wet look appearance.

ELEGANCE provides safety underfoot, good black heel mark resistance, exhibits instant burnish response and is designed for large high traffic areas requiring a consistent high gloss appearance and the mode of maintenance is auto scrubbing and Ultra High Speed burnishing.

ELEGANCE also contains a unique preservative system that aids in the prevention of bacterial growth when floors are properly maintained. E.g. Proteus mirabilis, an organism associated with urine and other infections would be relatively quickly neutralized in contact with ELEGANCE in a nursing home or childcare facility where incontinence may be a problem. Tests show that E. coil, Staph. aureus and Ps. aeruginosa numbers are significantly reduced when in contact with ELEGANCE.

ELEGANCE is deemed to comply AS/NZS 4586 -1999 Slip Resistance of Pedestrian Surfaces for dry slip.

PHYSICAL PROPERTIES

Appearance	Opaque white liquid
Odour	Acrylic polymer
pH	8.5 – 9.5
Specific Gravity	1.022 ± 0.005
Percentage Volatiles	79.5 – 80.5
Coverage	50 – 80 m ² /litre (typical)

DIRECTIONS FOR USE:-

The floor surface must be thoroughly cleaned and dry. Old or discoloured polish should be stripped from the floor with LAZER SUPER Floor Stripper.

Note: When stripping waxes and polishes from timber floors, ALL PURPOSE STRIPPING EMULSION must be used. Lazer Super is unsatisfactory on timber floors as in some instances it may affect the seal.

Apply ELEGANCE undiluted, direct to the floor using your preferred application method. Thin coats are preferable to minimise dry times and provide quicker cure time. Allow each coat to dry before application of further coats.

To produce optimum results, one coat of AQUASEAL Semi Permanent Sealer is applied to fill and prepare the floor surface. After this procedure apply 3 - 4 Coats of ELEGANCE. Allow each coat to dry before application of further coats.

TDGLA 001

PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.

N.S.W. (02) 9674 3000 QLD. (07) 3260 1377 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219
Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421