

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

SUPER FINISH SEAL

TIMBER & CORK SEAL

TDSE04-1-1100

DESCRIPTION: -

SUPER FINISH SEAL is a highly concentrated blend of penetrating oils and synthetic resins formulated to produce a tough, durable finish on timber, cork, parquetry and composition flooring.

SUPER FINISH SEAL dries to a tough durable film that is unaffected by water, dilute acids and alkalis, alcohol or oil. Super Finish Seal prevents timber floors from drying out and splintering. It resists rubber bums and produces a rich finish that enhances and retains the original natural colours of the timber.

PHYSICAL PROPERTIES	
Appearance	Slightly viscous tan coloured liquid
Odour	Mineral solvent
Specific Gravity	0.895 ± 0.005
Percentage Volatiles	64.5 – 65.5%
Solubility in Water	Insoluble
Coverage	12 – 16m ² /litre

DIRECTIONS FOR USE: -

New Untreated Surfaces - Apply Peerless Super Finish Seal in accordance with label directions, observe cutback procedure and preparation details for subsequent coats of Peerless Seals. Apply Super Finish Seal with a lambswool applicator, working across the grain and finishing with the grain of the timber. Provide adequate ventilation during application; avoid puddling of excess seal and work away from sealed area. To provide optimum film, thickness, protection and aesthetic appeal, two coats of Super Finish Seal is recommended. The second coat within 24 hours of the first drying.

Aged Floors - Prior to application of Super Finish Seal the Floor must be pre-cleaned with Peerless "Timber Preclean", or if polish, sealer finish or wax has been applied, stripped with All Purpose Stripping Emulsion, rinsed with clean water and allowed to dry. When dry, cut the floor back with sand screen discs or sandpaper (100 - 120 grit). Sweep or vacuum all dust and "Tack Rag" if necessary. Apply two coats of Super Finish Seal using a lambswool applicator, applying across the grain and levelling with the grain of the timber. Leave 6 - 8 hours or preferably overnight between coats. For more detailed information, consult the "Peerless Program for Timber Floors" or "Peerless Program for Multi-Purpose Floors."

TDGLA 001

PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.
 N.S.W. (02) 9674 3000 QLD. (07) 3260 1377 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219
 Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421